

Dumbwaiter Model: ☐ P-300	□ MJ-500
Have you contacted your local code enforcement for safety requirements?	Yes □ No □
Is the dumbwaiter going to be installed in a residence?	Yes ☐ No ☐
Is there living space below the dumbwaiter shaft?	Yes□ No□
What will the dumbwaiter primarily be used for?	
How many times will the dumbwaiter be used?	_per
Where did you hear about us?	

L	1-800-409-5438 ~ 530-333-1953	
Jo	b or Business Name:	
Cc	ontractor's Name, Phone #, & Email:	
Sh	nip to address:	
	stallation address:	
	wners' Name & Phone #*Owners' information is for warranty records only. Powerlift does not contact the owner. Powerlift does not install or service dumbwaiters.	
1.	The finished floor to finished floor measurement:	
2.	2. The overall height of shaft:	
	2. The overall height of shaft:	
3.	. The finished shaft width and depth: (The distance from the finished wall surface to finished wall surface.)	
	Shaft Width:Shaft Depth: OR Desired Car Size: Car Width: Car Depth:	
4.	. The desired loading height. bottom floor: top floor: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.)	
5.	 Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to. 	
	**For clarity, stand on the bottom floor and face	
	the "Bottom Floor Opening" to properly mark the locations on the diagram.**	
6.	While facing each opening which side will the door handle be on? Left or Right Rails	
	Bottom floor:Top Floor: Opening at Opening a	
7.	Desired voltage for dumbwaiter: Single Phase - 208 V 230 V (extra for MJ-500)	
	☐ Three Phase - ☐ 208 V ☐ 230 V ☐ 460 V ☐ Width	
	Bottom Floor Opening	
8.	Dumbwaiter cars come with a 3" Lip.	
	No Lip requires a car gate.	
	□ 3" LIP □ NO LIP	
9.	Accessories / Special Instructions:	